

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 16-Feb-2016

Print date: 16-Feb-2016

Version: 6.0

Page 1/12

EUROTEAM
construction chemicals



EUROLASTIC_Primer_B1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

EUROLASTIC_Primer_B1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Sector of uses [SU]

SU 19: Building and construction work

Uses advised against:

Sector of uses [SU]

SU 21: Consumer uses: Private households (= general public = consumers)

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

Euroteam Bauchemie GmbH

An der Mühle 1
15345 Altlandsberg
Germany

Telephone: +49 (0) 33438 14790

Telefax: +49 (0) 33438 147929

E-mail: info@euroteam-bauchemie.de

Website: www.euroteam-bauchemie.de

E-mail (competent person): info@euroteam-bauchemie.de

1.4. Emergency telephone number

Labor, 24h: +49 (0) 162 2599220, Montag - Donnerstag 7:00 - 16:00; Freitag 7:00 - 13:00 +49 (0) 33438 1479 19 (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]:

| Hazard classes and hazard categories | Hazard statements | Classification procedure |
|---|--|--------------------------|
| flammable liquids (<i>Flam. Liq. 2</i>) | H225: Highly flammable liquid and vapour. | |
| Respiratory or skin sensitisation (<i>Skin Sens. 1</i>) | H317: May cause an allergic skin reaction. | |
| Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>) | H319: Causes serious eye irritation. | |
| STOT-single exposure (<i>STOT SE 3</i>) | H336: May cause drowsiness or dizziness. | |

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS02
Flame



GHS07
Exclamation mark

Signal word: Danger

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 16-Feb-2016

Print date: 16-Feb-2016

Version: 6.0

Page 2/12

EUROTEAM
construction chemicals



EUROLASTIC_Primer_B1

Hazard components for labelling:

ethylbenzene; XYLOL; ethyl acetate; butanone

hazard statements for physical hazards

| | |
|------|-------------------------------------|
| H225 | Highly flammable liquid and vapour. |
|------|-------------------------------------|

hazard statements for health hazards

| | |
|------|--------------------------------------|
| H317 | May cause an allergic skin reaction. |
|------|--------------------------------------|

| | |
|------|--------------------------------|
| H319 | Causes serious eye irritation. |
|------|--------------------------------|

| | |
|------|------------------------------------|
| H336 | May cause drowsiness or dizziness. |
|------|------------------------------------|

Supplemental Hazard information (EU)

| | |
|--------|---|
| EUH204 | Contains isocyanates. May produce an allergic reaction. |
|--------|---|

Precautionary statements Prevention

| | |
|------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
|------|--|

| | |
|------|---|
| P243 | Take precautionary measures against static discharge. |
|------|---|

| | |
|------|---|
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray. |
|------|---|

| | |
|------|---|
| P271 | Use only outdoors or in a well-ventilated area. |
|------|---|

| | |
|------|--|
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
|------|--|

Precautionary statements Response

| | |
|--------------------|--|
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
|--------------------|--|

| | |
|-------------|---|
| P337 + P313 | If eye irritation persists: Get medical advice/attention. |
|-------------|---|

Precautionary statements Storage

| | |
|------|-----------------------------------|
| P403 | Store in a well-ventilated place. |
|------|-----------------------------------|

Additional information:

Results of PBT and vPvB assessment: not applicable

2.3. Other hazards

Adverse physicochemical effects:

Vapours can travel considerable distances to a source of ignition where they can ignite, flash back, or explode. This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

| product identifiers | Substance name Classification according to Regulation (EC) No 1272/2008 [CLP] | Concentration |
|---|--|---------------|
| CAS No.: 141-78-6 EC No.: 205-500-4 REACH No.: 01-2119475103-46-XXXX | ethyl acetate STOT SE 3, Flam. Liq. 2, Eye Irrit. 2 Danger H225-H319-H336-EUH066 | 25 - 50 % |
| CAS No.: 78-93-3 EC No.: 201-159-0 | butanone STOT SE 3, Flam. Liq. 2, Eye Irrit. 2 Danger H225-H319-H336-EUH066 | 15 - 25 % |
| CAS No.: 26426-91-5 | 1,6-Hexamethylene diisocyanate, toluylene diisocyanate polymer Eye Irrit. 2, Skin Sens. 1 H317-H319 | < 10 % |
| CAS No.: 108-65-6 EC No.: 203-603-9 REACH No.: 01-2119475791-29-XXXX | 2-methoxy-1-methylethyl acetate Flam. Liq. 3 Warning H226 | < 10 % |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 16-Feb-2016

Print date: 16-Feb-2016

Version: 6.0

EUROTEAM
construction chemicals



Page 3/12

EUROLASTIC_Primer_B1

| product identifiers | Substance name Classification according to Regulation (EC) No 1272/2008 [CLP] | Concentration |
|---|---|---------------|
| CAS No.: 123-86-4 EC No.: 204-658-1 | n-butyl acetate STOT SE 3, Flam. Liq. 3 Warning H226-H336-EUH066 | < 10 % |
| CAS No.: 100-41-4 EC No.: 202-849-4 REACH No.: 01-2119489370-35-XXXX | ethylbenzene Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1 Danger H225-H304-H332-H373 | < 2 % |
| CAS No.: 1330-20-7 EC No.: 215-535-7 INDEX No.: 601-022-00-9 | XYLOL STOT SE 3, Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT RE 2, Asp. Tox. 1 Danger H226-H304-H312 + H332-H315-H319-H335-H373 | < 0.5 % |
| CAS No.: 4083-64-1 EC No.: 223-810-8 REACH No.: 01-2119980050-47-XXXX | p-toluenesulphonyl isocyanate STOT SE 3, Skin Irrit. 2, Eye Irrit. 2, Resp. Sens. 1 Danger H315-H319-H334-H335-EUH014 | < 0.5 % |

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Following inhalation:

Provide fresh air. Call a doctor if you feel unwell. If unconscious place in recovery position and seek medical advice.

In case of skin contact:

Remove mechanically (e.g. dab away using wadding or cellulose material) then thoroughly wash the affected skin with a mild cleansing agent and water.

After eye contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion:

Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO₂), Water spray

Unsuitable extinguishing media:

High power water jet

5.2. Special hazards arising from the substance or mixture

Gases/vapours, toxic

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

5.4. Additional information

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 16-Feb-2016

Print date: 16-Feb-2016

Version: 6.0

Page 4/12

EUROTEAM
construction chemicals



EUROLASTIC_Primer_B1

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Provide adequate ventilation. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.1.2. For emergency responders

No data available

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Other information:

Take up mechanically.

6.4. Reference to other sections

Safe handling: see section 7, Personal protection equipment: see section 8, Disposal: see section 13

6.5. Additional information

No data available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Fire prevent measures:

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharge. Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels:

Do not allow to enter into soil/subsoil.

Hints on storage assembly:

Keep away from food, drink and animal feedingstuffs.

Storage class: 3 - Flammable liquids

Further information on storage conditions:

Protect against: Frost. Keep container tightly closed. Keep only in the original container at a temperature not exceeding 30 °C (to be specified by the manufacturer). Store in a cool dry place.

7.3. Specific end use(s)

Recommendation:

No information available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 16-Feb-2016

Print date: 16-Feb-2016

Version: 6.0

Page 5/12

EUROTEAM
construction chemicals



EUROLASTIC_Primer_B1

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

| Limit value type (country of origin) | Substance name | ① long-term occupational exposure limit value ② short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark |
|--------------------------------------|--|--|
| TRGS 900 (DE) | ethyl acetate CAS No.: 141-78-6 | ① 400 ppm (1,500 mg/m ³) ② 800 ppm (3,000 mg/m ³) |
| IOELV (EU) | butanone CAS No.: 78-93-3 | ① 200 ppm (600 mg/m ³) ② 300 ppm (900 mg/m ³) |
| TRGS 900 (DE) | butanone CAS No.: 78-93-3 | ① 200 ppm (600 mg/m ³) ② 200 ppm (600 mg/m ³) |
| IOELV (EU) | 2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 | ① 50 ppm (275 mg/m ³) ② 100 ppm (550 mg/m ³) ⑤ (May be absorbed through the skin.) |
| TRGS 900 (DE) | 2-methoxy-1-methylethyl acetate CAS No.: 108-65-6 | ① 50 ppm (270 mg/m ³) ② 50 ppm (270 mg/m ³) |
| TRGS 900 (DE) | n-butyl acetate CAS No.: 123-86-4 | ① 62 ppm (300 mg/m ³) ② 124 ppm (600 mg/m ³) |
| IOELV (EU) | ethylbenzene CAS No.: 100-41-4 | ① 100 ppm (442 mg/m ³) ② 200 ppm (884 mg/m ³) ⑤ (May be absorbed through the skin.) |
| TRGS 900 (DE) | ethylbenzene CAS No.: 100-41-4 | ① 20 ppm (88 mg/m ³) ② 40 ppm (176 mg/m ³) |
| IOELV (EU) | XYLOL CAS No.: 1330-20-7 | ① 50 ppm (221 mg/m ³) ② 100 ppm (442 mg/m ³) ⑤ (May be absorbed through the skin.) |
| TRGS 900 (DE) | XYLOL CAS No.: 1330-20-7 | ① 100 ppm (440 mg/m ³) ② 200 ppm (880 mg/m ³) |

8.1.2. biological limit values

| Limit value type (country of origin) | Substance name | Limit value | ① parameter ② Test material ③ Sample time ④ Remark |
|--------------------------------------|-----------------------------------|--------------------|--|
| TRGS 903 (DE) | butanone CAS No.: 78-93-3 | 5 mg/L | ① 2-Butanon ② Urin ③ Expositionsende bzw. Schichtende |
| TRGS 903 (DE) | ethylbenzene CAS No.: 100-41-4 | 300 mg/g Creatinin | ① Mandelsäure + Phenylglyoxylsäure ② Urin ③ Expositionsende bzw. Schichtende |
| BAT (DE) | ethylbenzene CAS No.: 100-41-4 | 250 mg/g Creatinin | ① Mandelsäure + Phenylglyoxylsäure ② Urin ③ Expositionsende bzw. Schichtende |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 16-Feb-2016

Print date: 16-Feb-2016

Version: 6.0

Page 6/12

EUROTEAM
construction chemicals



EUROLASTIC_Primer_B1

| Limit value type (country of origin) | Substance name | Limit value | ① parameter ② Test material ③ Sample time ④ Remark |
|--------------------------------------|-----------------------------|-------------|--|
| TRGS 903 (DE) | XYLOL CAS No.: 1330-20-7 | 1.5 mg/L | ① Xylol ② Blut ③ Expositionsende bzw. Schichtende |
| TRGS 903 (DE) | XYLOL CAS No.: 1330-20-7 | 2,000 mg/L | ① Methylhipp ② Urin ③ Expositionsende bzw. Schichtende |

8.1.3. DNEL-/PNEC-values

| Substance name | DNEL value | ① DNEL type ② Exposure route |
|-----------------------------|----------------------|--|
| XYLOL CAS No.: 1330-20-7 | 289 g/m ³ | ① DNEL worker ② DNEL acute inhalative (systemic) |
| XYLOL CAS No.: 1330-20-7 | 77 g/m ³ | ① DNEL worker ② DNEL long-term inhalative (systemic) |
| XYLOL CAS No.: 1330-20-7 | 174 g/m ³ | ① DNEL worker ② DNEL acute dermal, short-term (local) |
| XYLOL CAS No.: 1330-20-7 | 180 g/m ³ | ① DNEL worker ② DNEL long-term dermal (systemic) |

| Substance name | PNEC Value | ① PNEC type |
|-----------------------------|------------|----------------------------|
| XYLOL CAS No.: 1330-20-7 | 0.327 mg/l | ① PNEC aquatic, freshwater |

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No data available

8.2.2. Personal protection equipment

Eye/face protection:

Eye glasses with side protection

Skin protection:

Suitable gloves type: NBR (Nitrile rubber) (0,8 mm). Breakthrough time (maximum wearing time): > 240 min DIN EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Respiratory protection:

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Suitable respiratory protection apparatus: Combination filtering device (EN 14387)

Other protection measures:

Keep away from food, drink and animal feedingstuffs. Wash hands before breaks and after work. Remove contaminated, saturated clothing immediately.

8.2.3. Environmental exposure controls

No data available

8.3. Additional information

No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: liquid

Colour: colourless

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 16-Feb-2016

Print date: 16-Feb-2016

Version: 6.0

EUROTEAM
construction chemicals



Page 7/12

EUROLASTIC_Primer_B1

Odour: like:Solvent

Safety relevant basis data

| parameter | | at °C | method | Remark |
|--|------------------------|-------|------------|---|
| pH | <i>not determined</i> | | | |
| Melting point/freezing point | <i>not determined</i> | | | |
| Freezing point | <i>not determined</i> | | | |
| Initial boiling point and boiling range | 79 °C | | | |
| Decomposition temperature (°C): | <i>not determined</i> | | | |
| Flash point | -4 °C | | | |
| Evaporation rate | <i>not determined</i> | | | |
| Ignition temperature in °C | 315 °C | | | |
| Upper/lower flammability or explosive limits | 1 - 11.5 Vol-% | | | Explosion group IIA |
| Vapour pressure | 104 hPa | 20 °C | | |
| Vapour density | <i>not determined</i> | | | |
| Density | 0.91 g/cm ³ | 20 °C | | |
| Bulk density | <i>not determined</i> | | | |
| Water solubility (g/L) | partially soluble | | | Reacts violently with water. |
| Partition coefficient: n-octanol/water | <i>not determined</i> | | | |
| Dynamic viscosity | 20 mPa*s | 20 °C | brookfield | |
| Kinematic viscosity | <i>not determined</i> | | | |
| Solvent content (%) | | | | VOC-value (in g/L): 790,1; Maximum VOC content: 86,83 % |

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Violent reaction with: Alcohols, Amines, Acid, Alkali (lye), Water. Danger of bursting container.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

In case of fire may be liberated: Gases, Isocyanates

Additional information

Handle and open container with care. Caution! Container under pressure.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 16-Feb-2016

Print date: 16-Feb-2016

Version: 6.0

Page 8/12

EUROTEAM
construction chemicals



EUROLASTIC_Primer_B1

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| CAS No. | Substance name | Toxicological information |
|-----------|---------------------------------|--|
| 108-65-6 | 2-methoxy-1-methylethyl acetate | LD₅₀ oral: >5,000 mg/kg (Rat) LD₅₀ dermal: >2,000 mg/kg (Rat) LC₅₀ inhalative: >4,345 ppmV 6 h (Rat) |
| 123-86-4 | n-butyl acetate | LD₅₀ oral: 10,760 mg/kg (Rat) OECD 423 LD₅₀ dermal: >14,112 mg/kg (Rabbit) OECD 402 LC₅₀ inhalative: 23.4 mg/l 4 h (Rat) |
| 1330-20-7 | XYLOL | LD₅₀ oral: 3,523 mg/kg ATE dermal: 1,100 mg/kg ATE inhalativ Gase: 11 ppmV |
| 100-41-4 | ethylbenzene | LD₅₀ oral: 3,500 mg/kg (Rat) LD₅₀ dermal: 15,400 mg/kg (Rabbit) ATE inhalativ Gase: 11 ppmV |
| 4083-64-1 | p-toluenesulphonyl isocyanate | LD₅₀ oral: 2,600 mg/kg (Rat) |

Acute dermal toxicity:

LD50: 4 h: 24123 mg/kg

Acute inhalation toxicity:

LC50: 193 mg/L

Skin corrosion/irritation:

Prolonged or repeated contact with skin or mucous membrane result in irritation symptoms such as redness, blistering, dermatitis, etc.

Eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation:

May cause an allergic skin reaction.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Aquatic toxicity:

No information available.

Additional ecotoxicological information:

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

12.2. Persistence and degradability

Additional information:

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 16-Feb-2016

Print date: 16-Feb-2016

Version: 6.0

Page 9/12

EUROTEAM
construction chemicals



EUROLASTIC_Primer_B1

12.3. Bioaccumulative potential

Accumulation / Evaluation:

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

| CAS No. | Substance name | Results of PBT and vPvB assessment |
|-----------|-------------------------------|------------------------------------|
| 141-78-6 | ethyl acetate | — |
| 1330-20-7 | XYLOL | — |
| 4083-64-1 | p-toluenesulphonyl isocyanate | — |

not applicable

12.6. Other adverse effects

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste according to applicable legislation.

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product:

| | |
|------------|--|
| 08 04 10 | waste adhesives and sealants other than those mentioned in 08 04 09 |
| 08 04 09 * | Waste adhesives and sealants containing organic solvents or other dangerous substances |
| 08 04 12 | adhesive and sealant sludges other than those mentioned in 08 04 11 |
| 08 04 11 * | adhesive and sealant sludges containing organic solvents or other dangerous substances |

*: Evidence for disposal must be provided.

Remark:

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Waste code packaging:

| | |
|----------|--|
| 15 01 01 | paper and cardboard packaging |
| 15 01 10 | packaging containing residues of or contaminated by dangerous substances |
| 15 01 02 | Plastic packaging |
| 15 01 04 | Metallic packaging |

Waste treatment options

Appropriate disposal / Product:

Dispose of waste according to applicable legislation.

Appropriate disposal / Package:

Dispose of waste according to applicable legislation.

13.2. Additional information

No data available

SECTION 14: Transport information

| Land transport (ADR/RID) | Inland waterway craft (ADN) | Sea transport (IMDG) | Air transport (ICAO-TI / IATA-DGR) |
|--------------------------------------|-----------------------------|----------------------|------------------------------------|
| 14.1. UN-No. | | | |
| 1866 | 1866 | 1866 | 1866 |
| 14.2. UN proper shipping name | | | |
| Resin solution | Resin solution | Resin solution | Resin solution |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 16-Feb-2016

Print date: 16-Feb-2016





Version: 6.0

Page 10/12

EUROTEAM
construction chemicals



EUROLASTIC_Primer_B1

| Land transport (ADR/RID) | Inland waterway craft (ADN) | Sea transport (IMDG) | Air transport (ICAO-TI / IATA-DGR) |
|---|--|---|--|
| 14.3. Transport hazard class(es) | | | |
|  3 |  3 |  3 |  3 |
| 14.4. Packing group | | | |
| II | II | II | II |
| 14.5. Environmental hazards | | | |
| No | No | No | No |
| 14.6. Special precautions for user | | | |
| Special provisions: transport category: 2 Limited quantity (LQ): 5L Hazard identification number (Kemler No.): 33 Classification code: - tunnel restriction code: D/E Remark: Excepted quantities (EQ): Code: E2 | Special provisions: transport category: 2 Limited quantity (LQ): 5L Classification code: - Remark: Excepted quantities (EQ): Code: E2 | Special provisions: Limited quantity (LQ): 5L EmS-No.: F-E; S-E Remark: Excepted quantities (EQ): Code: E2 | Special provisions: Limited quantity (LQ): Remark: Warning: Flammable liquids |

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
not applicable

Additional information:
Protect from moisture.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

No data available

15.1.2. National regulations

 **[DE] National regulations**

Störfallverordnung

Remark:

To follow: Störfallverordnung

Technische Anleitung Luft (TA-Luft)

Ziffer 1:

5.2.5.

Anteil 1:

86.8 %

Water hazard class (WGK)

WGK:

2 - deutlich wassergefährdend

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 16-Feb-2016

Print date: 16-Feb-2016

Version: 6.0

Page 11/12

EUROTEAM
construction chemicals



EUROLASTIC_Primer_B1

Technische Regeln für Gefahrstoffe

TRGS 900,400, 500, 510, 555, 600, 720, 721, 722, 430

Berufsgenossenschaftliche Vorschriften (BGV)

To follow: Berufsgenossenschaftliche Vorschriften (BGV) M 050, M 017, M 044, M 004

Relevante arbeitsmedizinische Vorschriften

To follow: Preventive industrial medical examinations are to be offered.

Other regulations, restrictions and prohibition regulations

To follow: Betriebssicherheitsverordnung (BetrSichV); Unfallverhütungsvorschrift: DGUV-V1; DGUV-V6

15.2. Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

15.3. Additional information

No data available

SECTION 16: Other information

16.1. Indication of changes

SECTION 2: Hazards identification

Label elements

SECTION 3: Composition / information on ingredients

SECTION 6: Accidental release measures

SECTION 7: Handling and storage

SECTION 8: Exposure controls/personal protection

SECTION 9: Physical and chemical properties

SECTION 10: Stability and reactivity

SECTION 11: Toxicological information

SECTION 12: Ecological information

SECTION 14: Transport information

SECTION 15: Regulatory information

SECTION 16: Other information

16.2. Abbreviations and acronyms

No data available

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Classification according to Regulation (EC) No 1272/2008 [CLP]:

| Hazard classes and hazard categories | Hazard statements | Classification procedure |
|---|--|--------------------------|
| flammable liquids (<i>Flam. Liq. 2</i>) | H225: Highly flammable liquid and vapour. | |
| Respiratory or skin sensitisation (<i>Skin Sens. 1</i>) | H317: May cause an allergic skin reaction. | |
| Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>) | H319: Causes serious eye irritation. | |
| STOT-single exposure (<i>STOT SE 3</i>) | H336: May cause drowsiness or dizziness. | |

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

| Hazard statements | |
|-------------------|---|
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H319 | Causes serious eye irritation. |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 16-Feb-2016

Print date: 16-Feb-2016

Version: 6.0

Page 12/12

EUROTEAM
construction chemicals



EUROLASTIC_Primer_B1

Hazard statements

| | |
|------|--|
| H332 | Harmful if inhaled. |
| H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H373 | May cause damage to organs through prolonged or repeated exposure. (...) |

16.6. Training advice

No data available

16.7. Additional information

No data available